

# LC1004N

License top mount  
170° view angle with night vision e

## CAMERA SPECIFICATION

Image Device	1/4" CMOS ASX340CS		
TV System	PAL	NTSC	
Effective Pixels	640*480pixels		
Sensing Area	4.077mm*3.136mm		
Scanning System	2:1 Interlace		
Sync. System	Internal		
Resolution	420TV Lines		
Horizontal Sync Frequency	15.625 kHz	15.734 kHz	
Vertical Sync Frequency	50 Hz	60 Hz	
Video Output	1.0Vp-p, 75Ohm		
Gamma Consumption	0.45		
AGC	Auto		
S/N Ratio	Better than 46dB		
White Balance	Auto		
Electronic Shutter	1/60(NTSC)/1/50(PAL)~1/100,000 Seconds		
BLC	Auto		
Operating Temperature	-20°C ~ 70°C, RH95%MAX		
Storage Temperature	-40°C ~ 80°C, RH95%MAX		
Power Supply	<input checked="" type="checkbox"/> DC12V	<input type="checkbox"/> DC10V~DC32V	
Waterproof rating	<input checked="" type="checkbox"/> IP69K	<input type="checkbox"/> IP67	<input type="checkbox"/> NONWATERPROOF
Viewing Angle	<input type="checkbox"/> 180°	<input type="checkbox"/> 160°	<input checked="" type="checkbox"/> 150° <input type="checkbox"/> 120° <input type="checkbox"/> 92°
Audio	<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No	
Minimum Illumination	<input checked="" type="checkbox"/> 0 Lux	<input type="checkbox"/> 0.1 Lux	
Night vision distance	<input checked="" type="checkbox"/> 3~5m	<input type="checkbox"/> 8~10m	<input type="checkbox"/> 12~15m
Image mode	<input type="checkbox"/> Mirror	<input type="checkbox"/> Normal	<input checked="" type="checkbox"/> Mirror/Normal image switch
Heater	<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No	