

2016



Vehicle Safety Solutions









2016 Vehicle Safety System Ford Transit Van Brake Light Camera

Mercedes Sprinter Van OE fit Back up Camera Kit



TransitCAM-A



TransitCAM-B





FM5000-FT Kit





SprinterCAM-2



OE Fit Ford Transit Van Kit

OEM Fit, easy Installation

-Special designed replacement third brake light cameras with wide view angle & night vision -Combine with OEM disinged replacement. HD 5" Rear view mirror monitor or 6", 7" LCD monitor to give a clear view behind the vehicle. Ensure your safety when reversing -Plug & Play designed, easy installation

FM 5000SP Kit

OEM Fit, easy Installation

-Special designed replacement third brake light cameras with wide view angle & night vision, buit-in Mic. -Combine with OEM disinged replacement. HD 5" Rear view mirror monitor or 6", 7" LCD monitor with Special bracket to give a clear view behind the vehicle. Ensure your safety when reversing -Plug & Play designed, easy installation







SprinterCAM-3



M6000-SP / M7000-SP







ExpressCAM-3



M6000-G, M7000-G



Nissan NV VAN OE fit Back up Camera Kit

Ford Transit OE fit Back up Camera Kit



OEM Fit, easy Installation

-Special designed replacement third brake light cameras with wide view angle & night vision, buit-in Mic(NV VAN only). -Combine with OEM disinged replacement. HD 5" Rear view mirror monitor or 6", 7" LCD monitor with Special bracket to give a clear view behind the vehicle. Ensure your safety when reversing -Plug & Play designed, easy installation





OEM Fit, back up camera kit:

-OEM style replacement rear view mirror 5" LCD monitor -OEM style replacement license light HD color wide view angle camera -Or top mount HD color wide view angle camera -Plug & play designed kit, easy installation



FM5000-TL Kit





Lip mount FT1000L

Up mount TR-CAM



FM5000-TCKit

OE Fit License Plate Light Replacement Camera for FORD E Series Commercial Vans











M6000 / M7000 / M7000QUAD





FM5000M-CB Kit

Commercial Truck & School Bus Back Up Camera Kit

-Special designed top mount HD camera with IR night vision, buit-in Mic. -Build in LED brake light for replace existing brake light into camera -Option for replacement rear view mirror 5" LCD color monitor or stand alone 6" or 7" LCD color monitor -Plug & play designed, fit for most cargo truch & VANs. easy installation -Fit for most Commercial Box Truck, Bus, School Bus & Fleet Service Vehicles



E-CAM



FM5000-EV Kit

Specs:

-OE Fit for Ford E-Series van

-OEM style replacement rear view mirror 5" wide screen digital LCD screen at center -OE Fit Special license plate light replacement night HD camera -2 camera inputs, option for 2nd camera -Automatically image on when in reverse gear -Plug & Play designed, easy installation







V1003N



C3000HN





BusCam

NEW PRODUCT

OE Fit Third Brake Light Replacement Camera for Europe Commercial Vans



Pick up Truck OE fit Back up Camera Kit







Ford F150





2015 F150

2013 Silverado

OEM Style Pick up Truck Back up Camera Kit

-OEM fit replacement rear view mirror 5" LCD monitor -Special designed tailgate handle mount wide view angle HD color camera -Plug & play designed kit, easy installation -The kit fits for FORD, GM, TOYOTA, DODGE, NISSAN and others

ТАСОМА

Camera						License mou		
		C1003S - Mini lip mount camera - Resolution: 480 TV lines - Minimum Illumination: 1.0Lux@F1.2 - Parking line: On or Off switchable - Image: Mirror or Non mirror switchable - Working voltage: DC 10 ~15V - View angle: 160 degree		C1002S -Lip mount camera Resolution: 480 TV line -Minimum illumination: <1 Lux -View angle: 170 degree -Image: mirror/non mirror switchable -Parking guild line: On/Off switchable -Working voltage: DC 10 -15 V		LB1000S		
		C1103 - Mini lip mount camera - Resolution: 480 TV lines - Minimum Illumination: 1.0Lux@F1.2 - Parking line: On or Off switchable - Image: Mirror or Non mirror switchable - Working voltage: DC 10 ~15V - View angle: 160 degree		C1007S - Plug in OEM style lip mount camera - Resolution: 480 TV lines - Minimum Illumination: 1.0Lux@F1.2 - Parking line: On or Off switchable - Image: Mirror or Non mirror switchable - Working voltage: DC 10 ~15V - View angle: 160 degree		LB1001N		
		SQ1000S - Mini square lip mount camera - Resolution: 480 TV lines - Minimum Illumination: 1.0Lux@F1.2 - Parking line: On or Off switchable - Image: Mirror or Non mirror switchable - Working voltage: DC 10 ~15V - View angle: 160 degree		C1008S - Mini Bee type lip mount camera - Resolution: 480 TV lines - Minimum Illumination: 1.0Lux@F1.2 - Parking line: On or Off switchable - Image: Mirror or Non mirror switchable - Working voltage: DC 10 ~15V - View angle: 160 degree				
		F2000S - Mini flat mount camera - Only 18.5mm diameter - Resolution: 480 TV lines - Minimum Illumination: 1.0Lux@F1.2 - Parking line: On or Off switchable - Image: Mirror or Non mirror switchable - Working voltage: DC 10 ~15V - View angle: 160 degree		F1000N - Flat mount camera with night vision - Resolution: 420 TV lines - Minimum Illumination: 0Lux with IR night vision - Parking line: On or Off switchable - Image: Mirror or Non mirror switchable - Working voltage: DC 10 ~15V - Operating Temperature: -30~+70 C - Lens Angle: 135 degree		0000		
		SQ1001N - Mini square lip mount night vision camera - Resolution: 480 TV lines - Minimum Illumination: OLux@F1.2 - Parking line: On or Off switchable - Image: Mirror or Non mirror switchable - Working voltage: DC 10~15V - View angle: 160 degree		C3600S - Mini Lip mount plug-in style 360 degree view angle adjustment - Resolution: 480 TV Line - Minimum illumination: 0.5 Lux - View angle: 180 degree - Working Voltage: DC 9-16 V - Parking guard line: On/Off switchable - Image: Mirror/Non mirror switchable				
	10	OEM-AE1000/AE1001S - Lip mount camera for Toyota - Resolution: 420 TV line - View angle: 170 degree - Minimum illumination: < 1 Lux - Distance guard line - Working voltage: DC 10 -15 V		C1001N - Lip mount camera with night vision - Resolution: 420 TV lines - Minimum Illumination: 0Lux with IR night vision - Parking line: On or Off switchable - Image: Mirror or Non mirror switchable - Working voltage: DC 10 ~15V - Operating Temperature: -30~+70 C - Lens Angle: 135 degree				

- Lens Angle: 135 degree

ount camera





- Mini license bar dual mount camera
- Resolution: 480 TV lines
- Minimum Illumination: 1.0Lux@F1.20(LB1000S) 0 Lux@F1.2(LB1001N)
- Parking line: On or Off switchable
- Image: Mirror or Non mirror switchable
- Working voltage: DC 10 ~15V
- View angle: 160 degree

LC1003S

- Mini license bar mount camera
- Resolution: 480 TV lines
- Minimum Illumination: 1.0Lux@F1.2
- Parking line: On or Off switchable
- Image: Mirror or Non mirror switchable
- Working voltage: DC 10 ~15V
- View angle: 160 degree

SensorCAM-2

- Combine two sensor and camera, show the image and distance on the monitor. With LED digit light night vision, detection range:120°
- OSD color distance and park line show on the screen.
- HD camera and wide angel:170°
- Alarm type: Beep Tone High quality and easy install
 Voltage: DC 12V Ultrasonic Frequency: 40KHz
- Detecting Distance: 0.3-2.0M.

LC1004N

- License lip mount night vision camera,
- Easy to install
- Resolution: 420 TV line
- View angle: 170 degree
- Minimum illumination: 0 Lux
- Distance guard line on/off control
- Working voltage: DC 10 -15 V

PlateCam1000

- License frame night vision camera,
- Easy install
- Resolution: 420 TV line
- View angle: 170 degree
- Minimum illumination: 0 Lux
- Working voltage: DC 10 -15 V



Camera for commercial vehicle

NEW	- He - Cu - Se - Hic - Se - Hic - Vic - Min - Vic - TV - Vic - An - Wa - Wa - Wa - Op
	- Nig - Re - Vie - Prr - Min - Ima - Wo
	- Nig - Re - Vie - Pre - Min - Ima - Wo
	- Sta - Re - Vie - Min - Ima - Wo
	- He - Op - Re - Vie - Vie - Min - Wo
	S1 - Nig - Op - Re - Vie - Min - Ima - Wo
	- He for - Re - Vie - Wa - Wo

13

C3000HN

leavy duty night vision camera for commercial vehicle current Consumption: MAX: 120mA ensor: Supper CMD High performance Digital Image Sensor ligh Resolution: 580 TV Line finimum illumination: 0 Lux with IR fiew angle: 175 degree ffective Pixies: 762 x 504 V System: NTSC fideo colour: Full colour nti fog lens Vaterproof: IP68 Vorking Voltage: DC 9-35 V Operating Temperature: -30 to 70 C

usCAM-20

light vision truck or bus camera, tesolution: 420 TV line View angle: 135 degree Pre-heated function for cold weather Minimum illumination: 0 Lux nage: mirror/non mirror with distance guard line on/off control Vorking voltage: DC 10 -15 V

usCAM-30

light vision truck or bus camera, tesolution: 420 TV line fiew angle: 135 degree Pre-heated function for cold weather finimum illumination: 0 Lux nage: mirror/non mirror with distance guard line on/off control Vorking voltage: DC 10 -15 V

usCAM-10

tainless Heavy duty night vision truck or bus camera tesolution: 420 TV line 'iew angle: 135 degree finimum illumination: 0 Lux nage: mirror / non mirror control Vorking voltage: DC 10 -15 V

omeCAM

leavy duty Dome mount night vision camera Option for wall mount or roof mount Resolution: 420 TV line View angle: 135 degree Minimum illumination: 0 Lux Vorking voltage: DC 10 -15 V

1000S-R/L

light vision commercial truck rear or side mount camera Option for rear, left side or right side view mount lesolution: 420 TV line fiew angle: 135 degree Minimum illumination: 0 Lux nage: mirror / non mirror control Vorking voltage: DC 10 -15 V

ualCAM

leavy duty night vision Dual camera or commercial vehicle Resolution: 420 TV Line View angle: 135 degree Vaterproof: IP67-IP68 Vorking Voltage: DC 9-16 V

Rear view monitor

	1
	OEM-FM5000M
	-OEM style replacement rear view mirror -5" wide screen (16:9) LCD digital screen -2 camera inputs
	-Auto rear view camera connection -Easy installation, fit for most passenger vehicle
	-Camera is option -Working voltage: DC 10-15V -Special Bracket for Sprinter Van, GM, Toyota, Honda & Dodge
	OEM-TM4300DL
	-OEM style replacement rear view mirror -4.3" wide screen (16:9) LCD digital screen
	-2 camera inputs -Auto rear view camera connection
	-Easy installation, fit for most passenger vehicle -Camera is option -Working voltage: DC 10-15V
	-Special Bracket for Sprinter Van, GM, Toyota & Honda
	OEM-FM4300L OEM-FM4300DVR
	- OEM style replacement rear view mirror - 4.3" wide screen (16:9) LCD digital screen
	- 2 camera inputs - Auto rear view camera connection
	- Easy installation, fit for most passenger vehicle -Camera is option
	- Working voltage: DC 10-15V - Special Bracket for Sprinter Van, GM, Toyota, VW & Honda
	- OEM style replacement of clip on rear view mirror
Star Star	- 4.3" wide screen (16:9) digital LCD screen - 2 camera inputs
	- Option for Replacement (TR4300) or clip on (TC4300) - Auto rear view camera connection
	- Easy installation, fit for most passenger vehicle - Working voltage: DC 10-15V
	-Special Bracket for GM, Toyota, VW & Honda
	RM4300 (Replacement), RC4300 (Clip on)
	 OEM style replacement of clip on rear view mirror 4.3" wide screen (16:9) digital LCD screen
	- 2 camera inputs - Option for Replacement (RM4300) or clip on (RC4300)
	- Auto rear view camera connection - Easy installation, fit for most passenger vehicle
	- Easy installation, in for most passenger vehicle - Working voltage: DC 10-15V -Special Bracket for GM, Toyota, VW & Honda
	<u>MC7000</u>
	-Clip on rear view mirror -7" wide screen (16:9) TFT LCD screen
C Anterna	-2 camera inputs -Auto rear view camera connection
	-Remote control -Working voltage: DC 10-15V
	, , , , , , , , , , , , , , , , , , ,

Monitor

AE4300HD

- All new designed high resolution 4.3" digital monitor
- Universal mount slim design for Dash mount, Windshield mount - Auto reversing camera connection
- Fully auto image self control with plug & play feature
- Working voltage: DC 10-15V
- Option with parking sensor





Dash mount

Windshield mount



All new 3.5" digital touch-screen monitor



Dual mount filip-in 4.2" LCD monitor



- Universal mount slim design for Dash mount, Windshield mount & Roof mount
- Auto reversing camera connection
- Fully auto image self control with plug & play feature
- Working voltage: DC 10-15V

BC3500D

- 3.5" digital LCD monitor with wide view angle and high resolution
- Multi-languages of display available.
- Working voltage: DC 10~16V. with2 AV inputs & built-in speaker
- Automatically switches to back-up camera
- Touch-screen operation

RM42DUAL RM42DUAL-WL

- 4.2" Dual mount filip-in LCD monitor
- Unique design for dash mount
- Auto reversing camera connection(Wireless)
- High resolution image
- 1 video input
- Working voltage: DC 10-15V

Monitor

M3800 M5000U - 3.8", 5" universal mount wide screen digital image high resolution LCD monitor - 1 AV or 2 AV input - PAL & NTSC auto switching - Built in speaker - Auto rear view camera connection - Working voltage: DC 12V M6000 - 6" dash mount wide screen digital image high resolution LCD monitor - 2 AV inputs - PAL & NTSC auto switching - Resolution: 1440 x 234 dots - Built in speaker - Auto rear view camera connection - Remote control, OSD menu - Working voltage: DC 12 - 24V compatible M7000 M7000U - 7" dash mount wide screen high resolution LCD monitor - 2 AV inputs - PAL & NTSC auto switching - Resolution: 1440x234 dots - Built in speaker - Remote control, OSD menu - Working voltage: DC 12 - 24V compatible M7300 - 7" dash mount wide screen high resolution LCD monitor - 3 AV inputs With 3 trigger wires for control 3 cameras - PAL & NTSC auto switching - Resolution: 1440x234 dots - Built in speaker - Remote control, OSD menu - Working voltage: DC 12 - 24V compatible M7400QUAD - 7" color LCD monitor with built-in quad - Single, dual, triple, quad image and PIP functions available - Four camera inputs plus one DVD AV input and two video outputs - The display effect, volume and mirror function for each camera can be separately set up - The priority of quad picture and dual picture can be set up - With trigger wire for dual picture, the relative cameras can be combined optionally

- Four trigger wires for auto connector each camera
- Backup distance grid & left / right-turning indicator arrow available.

- Working voltage: DC 12~32V



	-
	System H3500A Includes: HD3500 3.5" HD LCD monitor C1103 lip mount HD camera Cables
	System H3500C Includes: HD3500 3.5" HD LCD monitor LC1003S mini license bar camera Cables
NEW	System H4300E Includes: HD4300 4.3" HD LCD monitor TH1000S truck tailgate camera Cables
	System H4300B Includes: HD4300 4.3" dash HD monitor LC1003S mini license bar camera Cables
	System H4300D Includes: HD4300 4.3" dash HD monitor C1004N plate lip night vision camera Cables



System H3500B

Includes: HD3500 3.5" HD LCD monitor F2000 flash mount HD camera Cables



System H3500D

Includes: HD3500 3.5" HD LCD monitor LB1000S back plate mount camera Cables



System H4300A

Includes: HD4300 4.3" dash HD monitor C1103 lip mount HD camera Cables



System H4300C

Includes: HD4300 4.3" dash HD monitor F2000 flash mount HD camera Cables



System H4300E

Includes: HD4300 4.3" dash HD monitor TH1000S truck tailgate camera Cables

Back up camera system kit

Back up camera kit for commercial vehicle



Two Cameras System Kit

System C6002A System C7002A

Includes: M6000 6" LCD monitor M7000 7" LCD monitor BusCAM20 night vision camera C2000 Side camera 50 Feet cable x 2

System C6002B System C7002B

Includes: M6000 6" LCD monitor M7000 7" LCD monitor BusCAM30 night vision camera S1000N Side camera left or right 50 Feet cable x 2

System C6002C System C7002C

Includes: M6000 6" LCD monitor M7000 7" LCD monitor S1000N Left side night vision camera S1000N right night vision Side camera 50 Feet cable x 2

System C6002D System C7002D

Includes: M6000 6" LCD monitor M7000 6" LCD monitor BusCAM20 night vision camera Done night vision camera 50 Feet cable x 1, 20 Feet cable x 1









Back up camera kit for commercial vehicle

Three Cameras Kit

System C7003A



Includes: M7000 7" LCD monitor BusCAM30 night vision camera S1000N left side camera S1000N right side camera 50 Feet cable x 3

System C7003B

BusCAM20 night vision camera

M7000 7" LCD monitor

C5000N left side camera

50 Feet cable x 3

C5000N right side camera

Includes:



System C7404A-QUAD

Four cameras QUAD system Kit

Includes: 7" color LCD monitor with built-in quad control for 4 AV in put BusCAM20 night vision camera (Rear) C5000N left side camera C5000N right side camera BusCAM30 night vision camera (Front) 50 Feet cable x 4

System C7404B-QUAD

Includes:

7" color LCD monitor with built-in quad control for 4 AV in put BusCAM20 night vision camera (Rear) BusCAM30 night vision camera (Front) S1000N left side camera S1000N right side camera 50 Feet cable x 4

System C7101W Wireless



- Power supply: 12-24V±10%
 Built-in 2.4G wireless function, can receive audio/video
 4trigger signal, 2.4G 4point could switch
 2.4G in open area: 100M
 Built-in speaker. OSD menu, remote control
 Touch button screen
 - UP to two wireless camera (optional)

- 7 inch 16:9 LED back light monitor

- Resolution:800 × RGB × 480

- Image sensor: SHARP 1/4CCD
- Definition: 420TV line
- Minimum illumination: 0.5lux
- Image angle: 120°
- 2.4G wireless transmitter: 100M in open area
- Power supply: 12V-24V
- Water proof class : IP67/68
- Special for bus, truck.
- Heavy duty waterproof, shockproof night vision
- Working temperature: -20-60°C

Blind Spot Detection System

BSD1000

New designed aftermarket Blind Spot Detection System -Universal designed for all passenger car or mid size commercial van -2 high power Digital -Detection range: 3 to 10 Feet -2 LED warning indicator -Trigger on Beeper when signal light on -Detachable sensor cable -Working voltage: DC 10~15 V -Working temperature: -40 ~ 80°C



BSD1000P

New designed aftermarket Blind Spot Detection System Intergraded with rear parking sensor system -Universal designed for all passenger car or mid size commercial van -2 high power Digital -Detection range: 3 to 10 Feet -Display: 2 LED indicator plus dash mount LED distance display -Trigger on Beeper when signal light on -Detachable sensor cable -Working voltage: DC 10~15 V -Working temperature: -40 ~ 80°C

Auto-i Blind Spot Detection system (BSD system) is an assistant system with the advanced technology, it continuously monitor the blind spots on both sides of the vehicle to prevent blind spot-related lane-change accidents.

The system will work automatically when the turn signal is on. Two high performance ultrasonic sensors are mounted on both sides of the bumper. They work independently as a standalone unit for sending signals to a main ECU control module. The ECU will process the digital information data and transfer the indication signal to two LED warning indicators which are mounted inside the front side bar or inside the side mirror and give the driver a warning when any other vehicle is in the blind spot zone. The warning signal is made of both LED light flashing and Beeper tone to alert the driver and ensure the safety when making the lane change.



21




BSD1000D

New designed aftermarket Blind Spot Detection System

- -Universal designed for all passenger car or mid size commercial van -2 high power Digital
- -Detection range: 3 to 10 Feet
- -Display: 2 LED indicator plus dash mount LED distance display
- -Trigger on Beeper when signal light on
- -Detachable sensor cable
- -Working voltage: DC 10~15 V
- -Working temperature: -40 $\sim 80^\circ C$





Parking Sensor System



OEM-U404 OEM-P404V

- All new designed universal parking sensor
- Four sensors rear system
- Feet or Meter display
- Up or dash mount display reversible
- 2 channels LED distance indication
- Multi color selection with detachable cable
- Working voltage: DC 10-15 V
- Working temperature: -40c 80c
- Voice Option on OEM-U404V

<u>OEM-U</u>400

All new designed universal parking sensor

- 4 sensors rear system
- Up or dash mount display auto reversible
- 2 channels LED distance indication
- Multi color selection with detachable cable
- Working voltage: DC 10-15 V
- Working temperature: -40c 80c

OEM-F400 OEM-F400B

- Front Sensor system with 4 sensor
- Turn on with brake light
- Come with switch On/Off the system
- Distance detection: 0.3~2.0m or 1~6 feet
- Beep: Come with Beep tone On & Off switch.
- Detachable sensor cable 4.5m or 14 ft
- Working voltage: DC 10~15 V
- Option with LED display show the distance

OEM-R400

- All new designed universal parking sensor
- Four sensors rear system
- Feet or Meter display
- Up or dash mount display reversible
- 4 channels LED distance indication
- Sensitivity adjustable
- Multi color selection with detachable cable
- Working voltage: DC 10-15 V
- Working temperature: -40c 80c

OEM-P416

- All new designed universal parking sensor:
- Mini size 16mm Four sensors rear system
- Feet or Meter display reversible
- Up or dash mount display reversible
- 2 channels LED distance indication
- Sensitivity adjustable
- Multi color selection with detachable cable
- Working voltage: DC 10-15 V
- Working temperature: -40c 80c











Parking Sensor System

OEM-UB400

All new designed universal parking sensor

- 4 step Beeper tone with volume control
- Sensitivity adjustable
- Multi color selection
- Working voltage: DC 10-15 V
- Working temperature: -40c 80c

OEM-B400

All new designed universal parking sensor

- 4 step Beeper tone
- Sensitivity adjustable
- Multi color selection
- Working voltage: DC 10-15 V
- Working temperature: -40c 80c

OEM-R600/OEM-R800

All new designed universal parking sensor

- 6 or 8 sensors front & rear system
- Feet or Meter display
- Up or dash mount display reversible
- 4 channels LED distance indication
- Sensitivity adjustable
- Multi color selection with detachable cable
- Working voltage: DC 10-15 V - Working temperature: -40c - 80c
- Working temperature: 400 0

OEM-D600

- OEM-D600 Digital Parking Sensor System Front & Rea- New designed OE Digital processing.
- 2 sensor at front & 4 sensor rear system
- Fuse: Inside self-recovering fuse
- Distance detection: Rear: 0.1~2.0m or 1~6 feet or 0.1~3.0m or 1~7 feet. Front: 0.1~ 1.5m or 1~3 feet.
- Display: LED 4 channels indicator with numeric (Dash or Up mount)
- Detachable sensor cable for all 4 digital sensors
- Working voltage: DC 10~15 V
- Working temperature: -40 ~ 80c

Commercial Parking Sensor System





OEM-H401 OEM-H402

OEM-H401 Pick up Truck Parking sensor system Designed for pick up truck metal bumper with 25 feet long snesor cable Specification:

- 4 sensor at rear system with sleeve
- Fuse: Inside self-recovering fuse
- Distance detection: 0.3~1.8m or 1~5 feet
- Display: LED 2 channels indicator with
- numeric Meter or Feet and Dash or Up mount reversible. - Beep tone On/Off control.
- Detachable sensor cable for all 4 sensors
- Working voltage: DC 10~15 V
- Working temperature: -40 ~ 80c

<u>OEM-T401</u> <u>OEM-T402</u>

OEM-T401 Truck Parking sensor System Disigned for pick up truck metal bumper with 25 feet long snesor cable

- Specification:
- Heavy duty designed sensor..
- Fuse: Inside self-recovering fuse
- Distance detection: 0.3~1.8m or 1~5 feet
- Display: LED 2 channels indicator with
- numeric Meter or Feet and Dash or Up mount reversible. - Beep tone On/Off control
- Special under mount style sensor
- Detachable sensor cable for all 4 sensors
- Working voltage: DC 10~15 V
- Working temperature: -40 ~ 80c



OEM-CT4001

OEM-CT4001 for Heavy duty Commercial Truck Parking Sensor System Specification:

- New designed commercial truck Parking sensor system
- Working voltage: DC +12V
- Fuse: Inside self-recovering fuse
- Distance detection: 0.5~3m or 2~8 feet
- Multi Tone Buzzer with On/Off switch
- Sensor: Heavy duty design for metal bomper with 50 feet
- waterproof cable
- Working temperature: -40 ~ 80c



DVR-1080



M7400DVR-Q

Specification

Key feature and specifications:

Screen: Solution: Sensor: Lens Angel: Video Format: Picture Format: Photo Resolution: G-Sensor: Motion Sensor: Storage: Storage Temp: Working Temp: USB: Lens-in/HDMI: 2.4"TFT NTK 96650 AR0330 170° H.264,MOV JPEG 3M(Extend to 12M) Support support TF Card, Max 32G -20°~70°C -10°~70°C Support HDMI

7" QUAD Monitor with built-in DVR

-Back up camera system with up to 4 cameras

- -7" TFT-LCD color monitor dash mount
- -4 Video inputs,
- -DVR recording 4 channels video signal, VGA resolution640*480,
- -Recording speed: 60FPS, Storage format: AVI
- -Wide view angle
- -High quality picture 800x480 dots
- -Optional 12 V to 24 V power input
- -Auto power off function
- -Remote control
- -SD card option











The most reliable system Ensure your safety when driving.





Auto-i is a leading manufacture of Vehicle Safety System and is committed to continuously providing advanced reliable products to the mobile electronics market.

Auto-i(Canada)Corp.

Toronto, Canada www.auto-i.com

Online shopping: www.rearviewmaster.com

*